



Prospec Limited

Tel: 01709 377147

To complete the clause, select the appropriate wording from below. Highlighted text can be 'dragged and dropped' to save typing.

K32/120A PANEL CUBICLES - UNFRAMED

Prospec Ltd manufacture a range of panel cubicle systems, designed for durability, water and chemicals resistance, to withstand wet use, the rigours of cleaning and deter vandals.

Matching panels and other similar work

Use NBS clause K32/130A to include matching privacy screens. Use clause L20/480 for isolated cubicle fronts and doors in matching system.

Use NBS clause N10/350A for matching vanity units (without wash basins).

Use NBS clause K13/160A for matching wall linings.

Alternatively, add further clauses to section K32 to include matching panels and other similar work.

Click on the name below to jump to the product and specification details.

[Marathon 600 and 700 Cubicles](#)

Designed for use as changing and toilet cubicles in wet or dry areas.

Marathon 600 and 700 Cubicles

Designed for use as changing and toilet cubicles in wet or dry areas.

Constructed from Compact grade laminate or Solid surfacing materials. With specifically engineered aluminium fittings and components to overcome the weakness normally encountered in patch fitting systems.

Marathon Cubicles are installed by Prospec employees.

Consult Prospec Ltd technical literature for details and colour availability. Prospec also offers a design service with CAD drawings and it is recommended that they are consulted early in the design process.

Manufacturer: Prospec Limited, PO Box 48, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XP, Tel: 01709 377147, Fax: 01709 375239, Web: www.prospec.co.uk E-mail: marathon@prospec.co.uk

Product reference: Marathon 600 and 700 Cubicles

Panels/ Doors:

12 / 13mm Compact grade laminate.

12mm / 18mm Solid surfacing material.

Finish: Select from manufacturer's range availability.

Colour: Select from manufacturer's range availability.

Edge treatment: All edges machined with radius corners to doors.

Fittings:

Extruded Satin anodised aluminium brackets and fittings fixed through doors and panels with stainless steel bolts / screws and nylon grommets.

Hinges, spring loaded for automatic open or closed function, from Satin anodised aluminium and stainless steel fitted to doors and panels with High bond double sided tape and stainless steel screws through nylon grommets into Satin anodised aluminium rosettes with eccentric adjustment feature.

Satin anodised aluminium hinge and lock blinds fixed to panels / doors with double sided tape.

Headrail: Satin anodised aluminium overhead stabilising bars, Satin anodised aluminium friction fit clamp / doorstop to adjacent pilaster panel, and Satin anodised connector to top edge of partition panels.

Legs:

Support legs to 600 system

2no attached to front pilaster with clamp detail from Satin anodised aluminium and stainless steel with adjustable ground clearance.

Support legs to 700 system

1no attached to partition panel 150mm inboard with through fixings from Satin anodised aluminium and stainless steel with mechanical connection to front pilaster from Satin anodised aluminium with adjustable ground clearance.

Support posts connected mechanically to structural floor slab for large panels or partitions requiring joints and at external corners.

Ironmongery/ Accessories:

Choice of:

Door latch with outside indicator and emergency release function for toilet and changing cubicles, door buffer fitted to adjacent partition panel.

Mortice type door lock with Euro cylinder and lever furniture.

Internal aluminium doorknob with integral door buffer and external rosette.

External towel rail with internal doorknob with integral door buffer.

DDA compliant door latch available with matching grab handles to both sides of doors.

Door keeps fitted to pilaster panels with stainless steel bolts / screws and nylon grommets.

Satin anodised aluminium coat hooks on radius corner back plates, fixed with double-sided tape.

Outward opening doors fitted with hydraulic overhead closer or Door holder.

Other requirements:

Textured PVC curtains with bacteriostat, fire retardant BS5867 with Nickel-plated brass eyelets and white acrylic curtain rings

Integral Compact grade laminate bench seats.