



Prospec Limited
Tel: 01709 377147

To complete the clause, select the appropriate wording from below. Highlighted text can be 'dragged and dropped' to save typing.

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

145 VANITY / WASHROOM FURNITURE

Marathon Vanity Units

A system to match Marathon Cubicle systems (see NBS clauses K32/112, 120 and 130) and Marathon Back panel linings (see NBS clause K13/160). Materials and fittings for Marathon Cubicle and Vanity systems are selected for their durability and resistance to water and chemicals, to withstand wet use, the rigours of cleaning and to deter vandals.

Vanity Unit Type 1 – a half size vanity unit with cut out for protruding basin.

Vanity Unit Type 2 – a full-size vanity unit with integral cut out for basin and lower access panel

Typical Shelf - post formed and matching vanity units

Consult Prospec Ltd technical literature for details and colour availability. Prospec also offer a design services with CAD drawings and it is recommended that they are consulted early in the design process. Marathon Vanity Units are normally supplied only to site for installation by others.

The clauses below contain relevant headings that should be dragged and dropped and completed, where necessary, to complete the specification.

Marathon Vanity Units

Using Solid Surfacing Materials, Surell, Corian and other makes.

Solid surfacing, designed for long term, low maintenance use. It has solid colour throughout its thickness, virtually seamless joints and is water and mark resistant. A choice of inlays, colour bands and patterns are available.

Manufacturer: Prospec Limited, PO Box 48, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XP, Tel: 01709 377147, Fax: 01709 375239; Web: www.prospec.co.uk E-mail: marathon@prospec.co.uk

Product reference:

Marathon Vanity Unit Type 1

Marathon Vanity Unit Type 2

Marathon Vanity Unit Shelf

Material: Solid surfacing minimum thickness 10mm, bonded to moisture resistant 25mm MDF substrate machined to post-formed as detail with integral up-stand (if required), front down-stand, fascia ends where visible to be blocked in matching material and finish.

Colour/Texture: - select from manufacturer's range availability of colours, inlays, banding and textures).

Edge treatments: All exposed edges polished.

Size: - insert overall width of top height of up-stand, drop on down-stand, overall height of vanity unit as necessary.

Framing/Method of Support: - insert as necessary e.g. ex 35 x 50mm preservative treated softwood framing.

Fixings: - insert as necessary

Included features: - insert number and size of basin cut outs by vanity top supplier as necessary) e.g. cut-out for wash basin/taps/soap dispenser/tissue dispenser.

Components/Accessories: - insert as necessary e.g. panels and framing under Vanity unit as K13/160. Normally in compact grade/solid laminate.

Vanity Units

Using Composite Materials.

Formica high pressure laminate bonded to moisture resistant MDF or WPB plywood, minimum thickness 18mm with a compensate to reverse as necessary, post-formed to detail with integral up-stand (if required), front down-stand, fascia ends where visible to be blocked and laminate finished (see drawings for standard dimension). In a choice of standard colours from Formica sheet ranges.

Manufacturer: Prospec Limited, PO Box 48, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XP, Tel: 01709 377147, Fax: 01709 375239; Web: www.prospec.co.uk E-mail: marathon@prospec.co.uk

Product reference:

Marathon Vanity Unit Type 1

Marathon Vanity Unit Type 2

Marathon Vanity Unit Shelf

Materials:

18mm minimum thickness moisture resistant MDF

18mm minimum thickness WPB plywood

Adhesive: Moisture resistant

Joinery workmanship: As section Z10.

Size: - insert overall width of top height of up-stand, drop on down-stand, overall height of vanity unit as necessary.

Framing/Method of Support: - insert as necessary e.g. ex 35 x 50mm preservative treated softwood framing.

Fixings: - insert as necessary.

Other requirements: - insert number and size of basin cut outs by vanity top supplier as necessary) e.g. cut-out for wash basin/taps/soap dispenser/tissue dispenser; post-formed with integral rear/side up-stand, front down-stand, visible ends blocked and laminate finished.

Finish(es) as delivered: Fully bonded Formica high pressure laminate with a compensate to reverse.

Colour/Texture: - select from manufacturer's range availability of colours and textures.

Components/Accessories: - insert as necessary e.g. panels and framing under Vanity unit as K13/160.