


SUSPENDED

Product Summary



Features

- Option of a fully suspended system supported by connections to structural slab or walls above suspended ceiling
- The extruded aluminium hollow head section is capable of spans up to 6 metres of single depth wall mounted cubicles
- Vertical posts are mechanically joined to the head beam with screwport and through bolt connections to form a structural framework including capped ends
- Full length channels are used to attach partition and pilaster to walls
- Engineered to be used in double or single island configuration or wall mounted
- Suspended can be used in free standing block, between walls or with wall mounted supports concealed within the ceiling void
- Design flexibility enables it to be installed in almost any project, even with large ceiling voids, unlike traditional ceiling hung systems



SUSPENDED

Product Summary

K32/112A

Manufacturer: Prospec Limited, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XL, Tel: 01709 377147, Fax: 01709 375239, Web: www.prospec.co.uk E-mail: sales@prospec.co.uk

Product reference: Suspended

Overall Cubicle Height: 2083mm including floor clearance of 150mm.

Frame & Finish: Aluminium extrusions satin silver anodised to 25 microns **or** polyester powder coated.

Fittings: Extruded aluminium load bearing head beam and profiles.

Door Fittings: 3N^o solid colour nylon covered heavy-duty stainless steel / brass hinges per door; concealed nylon door latch with indicator and emergency release; standard handle assembly; DDA compliant handle set with lever action turn and horizontal grab handles; 1 coat hook per cubicle and 2 coat hooks to DDA compliant cubicles.

Pilasters, Doors & End Panels: 12mm compact grade laminate.

Partition Panels: 12mm compact grade laminate.

Edge Treatment: Bull-nosed with radiused corners.

Colour/Finish: Select from manufacturer's range availability.

Accessories: Anti-peep rails; anti-camera skirting; door holder for outward opening doors; door closers.

